

**IN THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

**Listing of Claims**

1. (canceled)

2. (previously presented) A seat assembly for a motor vehicle having a tub disposed at least partially in a floor of the vehicle, the seat assembly comprising:

a seat cushion translatable on at least one track to a position generally above the tub, the seat cushion being stowable in the tub wherein the at least one track is disposed generally laterally in the vehicle.

3—4. (canceled)

5. (previously presented) A seat assembly for a motor vehicle having a tub disposed at least partially in a floor of the vehicle, the seat assembly comprising:

a seat cushion translatable on at least one track to a position generally above the tub, the seat cushion being stowable in the tub wherein the at least one track is disposed generally laterally in the vehicle, and wherein the seat cushion is rotatable about an axis generally perpendicular to the at least one track.

6. (previously presented) The seat assembly of claim 2 further comprising at least one leg extending between the seat cushion and the at least one track.

7. (original) The seat assembly of claim 6 wherein the at least one leg is pivotably connected to the seat cushion.

8. (original) The seat assembly of claim 6 wherein the at least one leg is releasably connected to the at least one track.

9. (original) The seat assembly of claim 6 further comprising at least one second leg connected to the seat cushion, the at least one second leg being disposed inboard in the vehicle from the at least one leg.

10. (canceled)

11. (currently amended) A seat assembly for a motor vehicle having a floor, the seat assembly comprising:

at least one track disposed ~~at least partially in the floor;~~ generally laterally in the vehicle  
and

a seat cushion translatable on the at least one track to a position generally above the tub, the seat cushion being stowable in the tub wherein the seat cushion has an underside, and the underside presents a load floor when the seat cushion is stowed in the tub.

12. (original) The seat assembly of claim 11 wherein the load floor is generally even with the floor of the vehicle.

13—14. (canceled)

15. (previously presented) A seat assembly for a motor vehicle having a floor, the seat assembly comprising:

at least one track disposed generally laterally in the vehicle;

a tub disposed at least partially in the floor; and

a seat cushion translatable on the at least one track to a position generally above the tub, the seat cushion being stowable in the tub; and

at least one leg extending between the seat cushion and the at least one track; wherein the at least one leg is pivotably connected to the seat cushion.

16. (original) The seat assembly of claim 15 wherein the at least one leg is releasably connected to the at least one track.

17. (previously presented) The seat assembly of claim 15 further comprising at least one second leg connected to the seat cushion, the at least one second leg being disposed inboard in the vehicle from the at least one leg.

18. (currently amended) The seat assembly of claim ~~[[3]]~~ 2 wherein the seat cushion is rotatable about an axis generally perpendicular to the at least one track.

19. (currently amended) The seat assembly of claim ~~[[3]]~~ 2 further comprising at least one leg extending between the seat cushion and the at least one track.

20. (previously presented) The seat assembly of claim 19 wherein the at least one leg is pivotably connected to the seat cushion.